

REVISION TO 2006 STANDARD SPECIFICATIONS

SECTION 910, BEGIN LINE 143, DELETE AND INSERT AS FOLLOWS:

10. Dowel Bars

Dowel bars shall be plain billet steel in accordance with ASTM A 615, grade 40 (A 615M, grade ~~300~~ 280), except the bend test and elongation requirements will not apply. The dowel bar area and weight (mass) for the nominal bar diameter shall be as follows.

SECTION 910, BEGIN LINE 162, DELETE AND INSERT AS FOLLOWS:

~~Dowel bars will be jobsite sampled in accordance with the Frequency Manual and, when shipped to the project site, the bars shall be accompanied by the types of certifications specified in the Frequency Manual and in accordance with 916. As an alternate procedure, the dowel bars may~~ shall be furnished by selecting bars made by a coater and manufacturer on the list of approved Certified Reinforcing Bar Epoxy Coaters and in accordance with ITM 301. When shipped to the project site, the dowel bars shall be accompanied by the types of certifications specified in ITM 301 and in accordance with 916.

Other sections containing specific cross references:	General Instructions to Field Employees Update Required? Y___ N___ By - Additional or Revision
NONE	Frequency Manual Update Required? Y___ N___ By - Addition or Revision
Recurring Special Provisions potentially affected:	Standard Sheets potentially affected:
NONE	NONE
Motion: Mr.	Action: Passed as submitted; revised
Second: Mr.	Effective - _____ Letting
Ayes:	_____ Supplementals
Nays:	Withdrawn. Resubmit? _____
	Received FHWA Approval? _____